



Frascold[®] 68POE (Emkarate RL68H)

Typical Properties Data Sheet

Product Description:

Frascold 68POE is an ISO VG 68 synthetic polyol ester (POE) lubricant formulated specifically for use in refrigeration and air-conditioning compressors using HFC refrigerants. This product provides effective wear protection for steel and aluminium surfaces for increased system life and improved efficiency and is suitable for both initial fill and service fill. The combination of low temperature characteristics and unparalleled chemical and thermal stability enable the use of Frascold 68POE over a wide operating temperature range.

Analysis	Method	Typical value
Viscosity @ 40°C (cSt)	ASTM D445	66.6
Viscosity @ 100°C (cSt)	ASTM D445	9.4
Viscosity Index	ASTM D2270	120
Pour Point (°C)	ASTM D97	-39
Density @ 20°C (g/ml)	ASTM D1298	0.977
Flash Point COC (°C)	ASTM D92	270
Acid Value (mg KOH/g)	ASTM D974	< 0.05

These values are not intended for use in preparing specifications. Additional technical information such as water content is available upon request.

Frascold spa

Via Barbara Melzi 105, I-20027 Rescaldina (MI) ITALY
phone: +39-0331-742201, fax: +39-0331-576102
e-mail: frascold@frascold.it, www.frascold.it